

SUMITOMO'S HTR H4



H Rated High Performance All Season

- 1 Advanced Silica Tread Compound enhances traction for wet and snowy conditions and maintains superb dry road performance levels.
- 2 Computer Optimized Tread Design is designed for optimal balance, enhances grip and handling and promotes a quiet ride.
- 3 Multi-Pitched Variation Tread Blocks achieve noise reduction and minimizes irregular wear.
- 4 Shoulder Stabilized Tread Blocks offer predictable steering response and optimize traction and handling.
- 5 Warranty is our 50,000 Mile Limited Treadwear Warranty.



HTR H4

UTQG - 400 A A

Product Code	Tire Size	Service Description	Rim Range (inch)	Design Rim Width (inch)	PSI	Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Tread Width (inch)	Tread Depth (X/32")	Loaded Radius (inch)	Rolling Circum. (inch)	Revs per Mile	Weight (lbs.)
5516104	P195/70R14	90H	5.0-6.5	6.0	51	1,312	24.7	8.0	6.0	10	11.2	74.3	852	17.6
5516106	P175/65R14	81H	5.0-6.0	5.0	51	1,019	22.9	6.9	5.7	10	10.5	68.5	925	15.4
5516108	P185/65R14	85H	5.0-6.5	5.5	51	1,124	23.3	7.4	6.1	10	10.6	69.8	907	17.6
5516110	P195/65R14	88H	5.5-7.0	6.0	51	1,235	24.0	7.9	6.4	10	10.9	71.6	884	19.5
5516114	P185/65R15	86H	5.0-6.5	5.5	51	1,168	24.6	7.4	6.1	10	11.2	73.5	861	17.6
5516116	P195/65R15	89H	5.5-7.0	6.0	51	1,279	25.1	7.8	6.4	10	11.4	75.0	844	19.8
5516118	P205/65R15	92H	5.5-7.5	6.0	51	1,400	25.3	8.1	6.7	10	11.5	75.6	838	22.0
5516120	P215/65R15	95H	6.0-7.5	6.5	51	1,510	26.1	8.7	7.0	10	11.8	77.8	814	24.2
5516130	P185/60R14	82H	5.0-6.5	5.5	51	1,047	22.8	7.1	5.7	10	10.5	68.4	926	15.4
5516134	P195/60R14	85H	5.5-7.0	6.0	51	1,135	23.4	7.6	6.1	10	10.8	69.9	906	17.6
5516138	P205/60R14	88H	5.5-7.5	6.0	51	1,235	23.6	7.9	6.7	10	10.9	70.5	898	19.8
5516150	P195/60R15	87H	5.5-7.5	6.0	51	1,190	24.2	7.6	6.4	10	11.2	72.4	874	17.6
5516154	P205/60R15	90H	5.5-7.5	6.0	51	1,301	24.5	8.0	6.7	10	11.3	73.4	862	19.8
5516158	P215/60R15	93H	6.0-7.5	6.5	51	1,411	25.3	8.4	6.7	10	11.6	75.6	838	22.0
5516166	P215/60R16	94H	6.0-7.5	6.5	51	1,477	26.2	8.5	7.0	10	12.0	78.4	808	24.2
5516170	P225/60R16	97H	6.0-8.0	6.5	51	1,609	26.7	8.9	7.3	10	12.2	79.7	795	26.4
5516174	P205/55R16	89H	5.5-7.5	6.5	51	1,279	24.9	8.2	6.9	10	11.5	74.9	846	20.9
5516176	P215/55R16	91H	6.0-7.5	7.0	51	1,356	25.3	8.6	7.2	10	11.7	76.2	831	24.2
5516178	P225/55R16	94H	6.0-8.0	7.0	51	1,477	25.8	8.9	7.6	10	11.9	77.4	818	24.2
5516180	P235/55R16	96H	6.5-8.5	7.5	51	1,565	26.1	9.6	7.9	10	12.0	78.3	809	26.0
5516184	P225/55R17	95H	6.0-8.0	7.0	51	1,521	26.9	8.9	7.6	10	12.4	80.8	784	26.4
5516190	P225/50R16	91H	6.0-8.0	7.0	51	1,367	25.0	9.0	7.7	10	11.5	75.0	844	22.9
5516192	P245/50R16	96H	7.0-8.5	7.5	51	1,576	25.7	9.5	8.3	10	11.8	77.2	821	26.0