

## 2752MF

ORIGINAL | Lamps for printed circuit boards



### Areas of application

- Instrument and switch lighting

### Product benefits

- OEM Quality
- Wide product range
- Reliable quality

### Product features

- Original spare parts

## Technical data


### Electrical data

Power input	1.8 W
Nominal voltage	12.0 V
Nominal wattage	1.50 W
Power input tolerance	±10 %
Test voltage	13.5 V

### Photometrical data

Luminous flux	6.0 lm
Luminous flux tolerance	±20 %

### Dimensions & weight



Length	21.6 mm
Diameter	5 mm
Product weight	1.18 g

### Colors & materials

Base color	Beige
------------	-------

### Lifespan

Lifespan B3	1000 h
Lifespan Tc	6500 h

### Additional product data

Base (standard designation)	B8.5d
-----------------------------	-------

### Capabilities

Product datasheet

Thickness of PCB	1.6 mm
------------------	--------

Certificates & standards

ECE category	-
Approval marks – approval	-

Country specific categorizations

Order reference	2752MF 1,5W 12V
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321096760	OSRA2752MF	-	-	-

## Product datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321096760	2752MF	Unpacked 1	32 mm x 14 mm x 18 mm	0.01 dm <sup>3</sup>	4.17 g
4008321096777	2752MF	Folding carton box 10	27 mm x 46 mm x 113 mm	0.14 dm <sup>3</sup>	20.80 g
4008321096784	2752MF	Shipping carton box 50	148 mm x 55 mm x 115 mm	0.94 dm <sup>3</sup>	144.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.